

Aircraft 400 Hz Ground Power Supply Cable for high current, with concentric screen.

Type: **SXYJ 7X35+24X1/25**



35 mm², extra flexible, Conductor acc. to IEC 60228,6			
Properties	Nominal value	Tolerance	Unit
Wires in conductor, bare	1029	-	Pcs.
Wire diameter	0,20	± 0,02	mm
Resistance	0,546	+0,006	Ω/Km
Copper weight	305	-	Kg/km

1 mm², flexible, Conductor acc. to IEC 228,5			
Properties	Nominal value	Tolerance	Unit
Wires in conductor, bare	32	-	Pcs.
Wire diameter	0,19	± 0,02	mm
Resistance	19,0	+0,5	Ω/Km
Copper weight	8,3	-	Kg/km

Insulation of 35mm² acc. to HD 603			
Properties	Nominal value	Tolerance	Unit
Material	XLPE 90°C	-	-
Temperature range	-45 till +90		°C
Wall thickness	1,1	+ 0,2	mm
Outer diameter	10,5	+ 0,4	mm
Colour	2xBlack, 2xBrown, 2xWhite		

Insulation of 1mm² acc. to ISO 6722			
Properties	Nominal value	Tolerance	Unit
Material	PVC 100°C	-	-
Temperature range	-40 till +100		°C
Wall thickness	0,4	+ 0,1	mm
Outer diameter	2,1	+ 0,2	mm
Colour	Coloured coded		

Laying up of signal cores			
Properties	Nominal value	Tolerance	Unit
Lay Length	75	-50	mm
Construction	6x4		

Laying up of power cores and signal wires			
Lay Length	220	-50	mm
Centre core	Neutral 35mm ²		
Lapping helical tape	60		mm

Inner sheath acc. to HD 603			
Material	Filler	-	-
Temperature range	-55 till +80		°C
Outer diameter	40,8	+1,0	mm
Colour	Customer choice		

Concentric conductor S/Z, 25mm²			
Properties	Nominal value	Tolerance	Unit
Copper wires	16*1,16		mm
Lapping polyester foil	60*0,075		mm

Outer sheath acc. to HD 603			
Material	TP Rubber	-	-
Temperature range	-55 till +85		°C
Outer diameter	42,8	+1,0	mm
Colour	Customer choice		

Specific properties			
Properties	Nominal value	Unit	Standard
Voltage range	600/1000	V	
Routine voltage test, 5 min.	2.000	V	IEC 811
Type voltage test, 15 min. in water	4.000	V	IEC 811
Max. continuously current at ambient temp +30°C, per phase	324	A	IEC 204-1
Max. temperature for 5 sec	250	°C	
Max. short-circuit current for 5 seconds	4,2	kA	
Permissible minimum bending radius.	340	mm	DIN 0298-3
Flame Properties	Pass	Vertical	IEC 60332-1
Resistance 2 core at +20°C	0,267±0,01	Ω/Km	
Resistance 2 core at +70°C	0,320±0,01	Ω/Km	
Mutual capacitance	120	nF/km	
Inductance	0,093	mH/km	
Impedance	0,357	Ω/Km	
Voltage drop, φ=0,8	0,61	mV/Am	
Voltage drop, φ=0,8, 90kW, 25m, U ₀	2,87	V	
Weight, total	3,0	Kg/m	
Marking, ink printed	amokabel SXYJ 7X35+24X1/25		